

High Performance Portable Conveyors

TECHNICAL DATA SHEET

300 Series

LINKIT portable conveyors are ideal for working in confined spaces or areas where access is restricted such as basements, trenches, and backyards.



STANDARD FEATURES

- Hopper (32" L x 20" W)
- Folding Wheels*
- Linking Brackets
- Emergency Stops
- Trestle (20" H)
- Power Cord (3')

OPTIONAL ACCESSORIES

- Bulk Hopper (34" L x 38" W)
- Side Extensions
- Adjustable Trestle (40" H)
- Linking Cord (3')

MODEL	LKS300-3.2	LKS300-4.4	LKS300-5.5
DIMENSIONS	(10x12) 11" H x 126" L x 24" W	(14x12) 11" H x 174" L x 24" W	(18x12) 11" H x 213" L x 24" W
WEIGHT	228 lbs.	278 lbs.	309 lbs.
RATED CAPACITY**	Up to and above 60 metric Tph	Up to and above 60 metric Tph	Up to and above 60 metric Tph
RUBBER BELT	Vulcanized 2-ply poly reinforced w/ chevron	Vulcanized 2-ply poly reinforced w/ chevron	Vulcanized 2-ply poly reinforced w/ chevron
BELT CAPACITY	330 lbs.	330 lbs.	330 lbs.
BELT SPEED (Forward / Reverse)	92 ft/min (fast) 65 ft/min (slow)	92 ft/min (fast) 65 ft/min (slow)	92 ft/min (fast) 65 ft/min (slow)
MAXIMUM ANGLE	35 degrees	35 degrees	35 degrees
TEMPERATURE RATING	Motor: -13° F Belt: 15° F (min) / 185° F (max)	Motor: -13° F Belt: 15° F (min) / 185° F (max)	Motor: -13° F Belt: 15° F (min) / 185° F (max)
DRUM MOTOR	Rulmeca 0.55kW (1/2HP)	Rulmeca 0.55kW (1/2HP)	Rulmeca 0.55kW (1/2HP)
INVERTER	IMO Jaguar CUB5A-6J 110v 1-phase input / 220v 3-phase output	IMO Jaguar CUB5A-6J 110v 1-phase input 220v 3-phase output	IMO Jaguar CUB5A-6J 110v 1-phase input 220v 3-phase output
AMP DRAW	1.2 run / 5.0 peak	1.2 run / 5.0 peak	1.2 run / 5.0 peak
NOISE EMISSIONS	>75 dB	>75 dB	>75 dB

*Unit is not towable; **Actual throughput is subject to method of loading conveyor and type/consistency of material.