



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018  
Date Issued: 07/09/2015

Version: 1.2

**FOR CHEMICAL EMERGENCY:**  
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Name:** Gorilla Construction Adhesive

**Synonyms:** None

### Intended Use of the Product

Construction Adhesive

### Name, Address, and Telephone of the Responsible Party

#### **Company**

The Gorilla Glue Company  
2101 E. Kemper Road  
Cincinnati, Ohio 45241  
513-271-3300

[www.gorillatough.com](http://www.gorillatough.com)

### Emergency Telephone Number

**Emergency number** : 1-800-420-7186 (Prosar)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Skin Sens. 1 H317

Full text of H-phrases: see section 16

### Label Elements

#### **GHS-US Labeling**

#### **Hazard Pictograms (GHS-US)**

:



#### **Signal Word (GHS-US)**

: Warning

#### **Hazard Statements (GHS-US)**

: H317 - May cause an allergic skin reaction.

#### **Precautionary Statements (GHS-US)**

: P261 - Avoid breathing vapors, mist, or spray.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves.  
P302+P352 – IF ON SKIN: Wash with plenty of water.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

**Other Hazards:** Small amounts of methanol (CAS# 67-56-1) are formed by hydrolysis and released upon curing.

**Unknown Acute Toxicity (GHS-US)** 11.55% of mixture consists of ingredient(s) on unknown toxicity.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)
Limestone	(CAS No) 1317-65-3	30 - 60
Carbonic acid, calcium salt (1:1)	(CAS No) 471-34-1	10 - 30
Stearic Acid	(CAS No) 57-11-4	1 - 5
Quartz*	(CAS No) 14808-60-7	0.1 - 1



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018

Date Issued: 07/09/2015

Version: 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tin, dibutylbis (2,4-pentanedionato-O,O')-, (OC-6-11)-	(CAS No) 22673-19-4	0.1 - 1
--	---------------------	---------

\*Finely divided Quartz has caused cancer of the respiratory tract and lung disease in workers that inhaled it over an extended period of time. Studies suggest, however, that these hazards are not associated with other routes of exposure. The quartz in this formulation is in an adhesive matrix and is not expected to be "inhalable." Therefore, these hazards are not expected to be present.

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

**Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause allergic skin reactions.

**Inhalation:** None known.

**Skin Contact:** May cause skin irritation and/or allergic skin reactions.

**Eye Contact:** None known.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** None known.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Carbon dioxide, dry powder, water spray, and alcohol resistant foam.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not allow run-off from fire fighting to enter drains or water courses.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>).

### Reference to Other Sections

Refer to section 9 for flammability properties

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018

Date Issued: 07/09/2015

Version: 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### Environmental Precautions

Prevent entry to sewers and public waters.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container.

**Methods for Cleaning Up:** Dispose of waste safely and in accordance with local, state, federal, national, and international regulations.

### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep out of reach of children and animals.

**Incompatible Materials:** None known.

### Specific End Use(s)

Construction Adhesive

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Limestone (1317-65-3)		
USA NIOSH	NIOSH (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (respirable dust) 10 mg/m <sup>3</sup> (total dust)
USA OSHA	OSHA PEL (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (respirable fraction) 15 mg/m <sup>3</sup> (total dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
British Columbia	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (total dust)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (respirable fraction) 10 mg/m <sup>3</sup> (total dust)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline Silica)
Nunavut	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (respirable mass) 10 mg/m <sup>3</sup> (total mass)
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (respirable mass) 10 mg/m <sup>3</sup> (total mass)
Québec	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Limestone, containing no Asbestos and <1% Crystalline Silica-total dust)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	30 mppcf



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018  
Date Issued: 07/09/2015

Version: 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Yukon	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Mexico	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
<b>Carbonic acid, calcium salt (1:1) (471-34-1)</b>		
USA NIOSH	NIOSH (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (respirable dust)
USA NIOSH	NIOSH (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust)
<b>Quartz (14808-60-7)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 – Suspected Human Carcinogen
USA OSHA	OSHA PEL TWA (mppcf)	250 mppcf/% SiO <sub>2</sub> +5 (respirable fraction)
USA OSHA	OSHA PEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> /%SiO <sub>2</sub> +2 (respirable fraction)
USA OSHA	OSHA PEL TWA (mg/m <sup>3</sup> )	30 mg/m <sup>3</sup> /%SiO <sub>2</sub> +2 (total dust)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable particulate)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
Nunavut	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable mass) 0.3 mg/m <sup>3</sup> (total mass)
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable mass) 0.3 mg/m <sup>3</sup> (total mass)
Ontario	OEL Ceiling (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
Québec	VEMP (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (respirable dust)
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
Yukon	OEL TWA (mg/m <sup>3</sup> )	300 particle/mL
Mexico	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
<b>Tin, dibutylbis(2,4-pentanedionato-O,O'), (OC-6-11)- (22673-19-4)</b>		
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> Sn
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> Sn
USA NIOSH	NIOSH (TWA) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> except Cyhexatin Sn
USA IDLH	US IDLH (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup> Sn
USA OSHA	OSHA PEL (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> Sn
Mexico	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
<b>Methanol* (67-56-1)</b>		
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA NIOSH	NIOSH (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA NIOSH	NIOSH (STEL) (ppm)	250 ppm
USA NIOSH	NIOSH (STEL) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>
USA IDLH	US IDLH (ppm)	6000 ppm
USA OSHA	OSHA PEL (ppm)	200 ppm



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018

Date Issued: 07/09/2015

Version: 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA OSHA	OSHA PEL (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	200 ppm
Mexico	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	250 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup>

\*Small amounts of Methanol are formed by hydrolysis and released upon curing.

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective clothing. Safety glasses. Gloves.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Paste
Appearance	: White
Odor	: Musty
Odor Threshold	: Not available
pH	: Not applicable
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: > 93.3 °C (>200 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific gravity	: Not available
Density	: 1.7 g/cm <sup>3</sup>
Solubility	: Insoluble in water.



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018  
Date Issued: 07/09/2015

Version: 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available
VOC (%)	:	2
Solid Content (%)	:	95
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** None known.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures.

**Incompatible Materials:** None known.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Not available

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not available

**pH:** Not applicable

**Serious Eye Damage/Irritation:** Not available

**pH:** Not applicable

**Respiratory or Skin Sensitization:** Not available

**Germ Cell Mutagenicity:** Not available

**Teratogenicity:** Not available

**Carcinogenicity:** Not available

**Specific Target Organ Toxicity (Repeated Exposure):** Not available

**Reproductive Toxicity:** Not available

**Specific Target Organ Toxicity (Single Exposure):** Not available

**Aspiration Hazard:** Not available

**Symptoms/Injuries After Inhalation:** Not available

**Symptoms/Injuries After Skin Contact:** May cause skin irritation or an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Not available

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Not available

### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Limestone (1317-65-3)</b>	
Oral LD50 Rat	>5000 mg/kg
<b>Carbonic acid, Calcium salt (1:1) (471-34-1)</b>	
LD50 Oral Rat	6450 mg/kg
LD50 Dermal	> 2000 mg/kg
LC50 Inhalation Rat	> 3 mg/ml (Exposure time: 4 h)
<b>Stearic acid (57-11-4)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 5 g/kg



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018  
Date Issued: 07/09/2015

Version: 1.2

**FOR CHEMICAL EMERGENCY:**  
During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)

Oral LD50 Rat

>5000 mg/kg

## SECTION 12: ECOLOGICAL INFORMATION

**Toxicity** Not available

**Persistence and Degradability** Not available

**Bioaccumulative Potential** Not available

**Mobility in Soil** Not available

**Other Adverse Effects**

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Sewage Disposal Recommendations:** Do not dispose of waste into sewer.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

**In Accordance with DOT** Not regulated for transport

**In Accordance with IMDG** Not regulated for transport

**In Accordance with IATA** Not regulated for transport

**In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

**Gorilla Construction Adhesive**

TSCA – Toxic Substance Control Act

The ingredients in this product are listed within this act.

### US State Regulations

**Gorilla Construction Adhesive**

California Prop 65: This product contains one or more substances listed on Proposition 65 at or above 0.01 wt. %.

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (68515-49-1)

Quartz (14808-60-7)

Methanol (67-56-1)

### Canadian Regulations

**Gorilla Construction Adhesive**

WHMIS Classification

Class D Division 2 Subdivision B - Toxic material causing other toxic effects



The ingredients in this product are listed on or are exempt from the Canadian Domestic Substances List. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.



# Safety Data Sheet – Gorilla Construction Adhesive

Date Revised: 04/27/2018

Date Issued: 07/09/2015

Version: 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 04/27/18  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Skin Sens. 1	Skin sensitization Category 1
H317	May cause an allergic skin reaction

### HMIS

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

### Party Responsible for the Preparation of This Document

The Gorilla Glue Company  
+1 513-271-3300

*The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.*

Gorilla Construction Adhesive NA GHS SDS