HYDRAULIC BOX DUMPER - HBD-4-48

WARNING: CHECK STATE AND LOCAL CODES!!

APPROX WEIGHT: 1843.54 lbs.

SALES: X

34-007-037

SCALE: 1:32 FILE NAME:

09/30/2011

QUOTE # Χ

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE *** ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON 52" **INSIDE ROTATED** HEIGHT **LEVEL** HEIGHT 42" **DUMP** MAX HOLD HEIGHT **DOWN** FOR INTERNAL USE ONLY 18" PROJECT SIGN OFF MIN HOLD SALES **DOWN** ENG. 50" FAB. 68 1/2" DIMENSION TOLERANCE ± 1/4" **POWFR** STANDARD FEATURES HYDRAULIC BOX DUMPER NOTE: SINGLE PH. PLUG-IN UNITS WILL HAVE I. THE UNDERSIGNED, AGREE THAT THE PRODUCT AS APPROX 120 SEC DUMP / 33 SEC LOWER REPRESENTED SATISFIES DESIGN AND DIMENSION **MODEL NUMBER IS HBD-4-48** REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE Α CHUTE IS 52" W X 50" L (USABLE) PLEASE CIRCLE SPECIFICATIONS: Ρ DUMPER CAPACITY IS 4000 LBS. **POWER** AC. AIR/OIL Ρ **DUMP HEIGHT IS 48"** AND LOCAL REGULATIONS AND STANDARDS. R HOLD DOWN WILL ACCEPT BOXES MOTOR VOLTAGE 115 208 ANY MODIFIED UNITS ARE NON-RETURNABLE 0 18" TO 42" HIGH W/ HOLES EVERY 2" [] As drawn [] As marked DEDICATED CIRCUIT REQUIRED V FRAME WIDTH IS 69" **MOTOR PHASE** SINGLE **THREE** Α Signed: Date FRAME LENGTH IS 68 1/2" LEVEL HEIGHT IS 65" CONTROL HAND **FOOT Printed Name: ROTATED HEIGHT IS 129 1/2"** LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING ~ ALL BATTERY CHARGERS ARE 115V AC ~ DUMP ANGLE IS 45° DISTRIBUTOR'S NAME: BATTERY CHRG. **REMOTE** ON-BOARD CHROME PLATED CYLINDER WITH **VESTIL MANUFACTURING** W.O.# YES CHRG. INDICATOR NO **EMERGENCY STOP VELOCITY FUSE** DRAWN BY: CA PAINT IS VESTIL ROYAL BLUE

> SPECIAL FEATURES NONE

reference: X

Quoted lead time: $_{
m Y}$

* AVAILABLE AT ADDITIONAL COST