


# G-2130 / S-2130 Bolt Type Anchor Shackles

G-2130 Bolt type anchor shackles with thin head bolt - nut with cotter pin. Meets the performance requirements of Federal Specification RR-C-271F Type IVA, Grade A, Class 3, except for those provisions required of the contractor.

- Capacities 1/3 thru 150 metric tons, grade 6.
- Working Load Limit and grade "6" permanently shown on every shackle.
- Forged – Quenched and Tempered, with alloy pins.
- Hot Dip galvanized or Self Colored. (85, 120, and 150 metric ton shackles are all hot dip galvanized bows and the bolts are Dimetcoated® and painted red)
- Fatigue rated (1/3t - 55t).
- Shackles 25t and larger are RFID EQUIPPED.
- Approved for use at -40°C (-40°F) to 204°C (400°F).
- Meets or exceeds all requirements of ASME B30.26.
- Shackles 85 metric tons and larger are individually proof tested to 2.0 times the working load limit.
- Shackles 120 metric tons and larger are proof tested, Magnetic Particle Inspected and provided with Serialized Pin and Bow.
- Type Approval and certification in accordance with ABS 2006 Steel Vessel Rules 1-1-17.7, and ABS Guide for Certification of Cranes.
- 3.1 Certification as standard available for charpy and statistical proof test only up to 25 tons to DNV2.7-1 and EN13889.
- Crosby 2t through 25t G2130 anchor shackles are type approved to DNV Certification Notes 2.7-1- Offshore Containers. These Crosby shackles are statistical proof and impact tested to 42 joules

# the Crosby® group



Load Rated® Fatigue Rated®



MAXTOUGH®



(31 ft.-lbs.) min. ave. at -20°C (-4°F). The tests are conducted by Crosby and 3.1 test certification is available upon request.

- All other 2130 and all 2150 shackles can meet charpy requirements of 42 joules (31 ft.-lbs) avg. at -20°C (-4°F) upon special request.
- Look for the Red Pin®...the mark of genuine Crosby quality.

Nominal Size	Working Load Limit	Stock No.		Weight Each	Dimensions (in.)									Tolerance +/-	
		G-2130	S-2130		A	B	C	D	E	F	H	L	N	C	A
3/16	1/3 ‡	1019464	–	.06	.38	.25	.88	.19	.60	.56	1.47	.98	.19	.06	.06
1/4	1/2	1019466	–	.11	.47	.31	1.13	.25	.78	.61	1.84	1.28	.25	.06	.06
5/16	3/4	1019468	–	.22	.53	.38	1.22	.31	.84	.75	2.09	1.47	.31	.06	.06
3/8	1	1019470	–	.33	.66	.44	1.44	.38	1.03	.91	2.49	1.78	.38	.13	.06
7/16	1-1/2	1019471	–	.49	.75	.50	1.69	.44	1.16	1.06	2.91	2.03	.44	.13	.06
1/2	2	1019472	1019481	.79	.81	.64	1.88	.50	1.31	1.19	3.28	2.31	.50	.13	.06
5/8	3-1/4	1019490	1019506	1.68	1.06	.77	2.38	.63	1.69	1.50	4.19	2.94	.69	.13	.06
3/4	4-3/4	1019515	1019524	2.72	1.25	.89	2.81	.75	2.00	1.81	4.97	3.50	.81	.25	.06
7/8	6-1/2	1019533	1019542	3.95	1.44	1.02	3.31	.88	2.28	2.09	5.83	4.03	.97	.25	.06
1	8-1/2	1019551	1019560	5.66	1.69	1.15	3.75	1.00	2.69	2.38	6.56	4.69	1.06	.25	.06
1-1/8	9-1/2	1019579	1019588	8.27	1.81	1.25	4.25	1.33	2.91	2.69	7.47	5.16	1.25	.25	.06
1-1/4	12	1019597	1019604	11.71	2.03	1.40	4.69	1.29	3.25	3.00	8.25	5.75	1.38	.25	.06
1-3/8	13-1/2	1019613	1019622	15.83	2.25	1.53	5.25	1.42	3.63	3.31	9.16	6.38	1.50	.25	.13
1-1/2	17	1019631	1019640	19	2.38	1.66	5.75	1.53	3.88	3.63	10.00	6.88	1.62	.25	.13
1-3/4	25	1019659	1019668	33.91	2.88	2.04	7.00	1.84	5.00	4.19	12.34	8.80	2.25	.25	.13
2	35	1019677	1019686	52.25	3.25	2.30	7.75	2.08	5.75	4.81	13.68	10.15	2.40	.25	.13
2-1/2	55	1019695	1019702	98.25	4.13	2.80	10.50	2.71	7.25	5.69	17.90	12.75	3.13	.25	.25
3	† 85	1019711	–	154	5.00	3.30	13.00	3.12	7.88	6.50	21.50	14.62	3.62	.25	.25
3-1/2	† 120 ‡	1019739	–	265	5.25	3.75	14.63	3.62	9.00	8.00	24.88	17.02	4.38	.25	.25
4	† 150 ‡	1019757	–	338	5.50	4.26	14.50	4.00	10.00	9.00	25.68	18.00	4.56	.25	.25

\* **Note:** Maximum Proof Load is 2.0 times the Working Load Limit. Minimum Ultimate Strength is 6 times the Working Load Limit.

† Individually Proof Tested with certification.

‡ Furnished in Anchor style only and furnished with Round Head Bolts with welded handles.