

GLOBAL PURE™ PFAS WATER FILTER



BY GLOBAL INDUSTRIAL™

High Performance Filtration. Low Profile Design.

Enjoy cleaner water with this Global Pure™ Replacement Water Filter. Featuring a 3,600-gallon high-capacity advanced filtration system, this unit removes total PFAS and a full range of chlorine, lead, cyst, turbidity, and microplastics. This filter offers easy ¼ turn installation and is compatible with Global Industrial™ & Elkay® Filtered Water Bottle Refilling Stations and Filtered Coolers.

NSF/ANSI STANDARD 42

Substance	Influent Challenge Concentration	% Reduction Requirement/Max. Permissible Product Water Concentration	Average % Reduction
Chlorine	2.0 mg/L ± 10%	≥ 50%	98.78%
Particulate, Class I particles 0.5 to < 1 µm	At least 10,000 particles/mL	≥ 85%	98.60%

NSF/ANSI STANDARD 53

Substance	Influent Challenge Concentration	Min. Reduction Requirement/Max. Permissible Product Water Concentration	Average % Reduction
Lead pH 6.5	0.15 mg/L ± 10% mg/L	0.010 mg/L	98.70%
Lead pH 8.5	0.15 mg/L ± 10% mg/L	0.010 mg/L	98.24%
Cyst	min. 50,000/L	99.95%	99.99%
Turbidity	11+/- 1 NTU	0.5 NTU	>99.5%
Total PFAS (PFOA + PFOS, PFNA, PFHxS, and PFHpA)	0.00216+/- 20%	0.010 ug/L	98.05

NSF/ANSI STANDARD 42

Substance	Influent Challenge Concentration	% Reduction Requirement/Max. Permissible Product Water Concentration	Average % Reduction
Microplastic	at least 10,000 particles/ml	>/- 85%	98.60%

Not all water will contain contaminants listed. Testing performed under standard laboratory conditions; actual performance may vary. Filter usage must comply with all state and local laws. Filter is only to be used with cold water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

HIGHLIGHTS

- ✓ 3,600-gallon high-capacity advanced filtration system
- ✓ Compatible with WaterSentry® Filters
- ✓ NSF/ANSI Listed (Standards 42, 53, 372 & 401) with total PFAS filtration (PFOA + PFOS, PFNA, PFHxS, and PFHpA)



1/4 turn for easy installation and quick disconnect